

KUBE-8060

Fanless Digital Signage Player with Intel® Calpella platform



- Fanless Compact Size with Intel® Calpella platform
- 2x DDR3 800/1066 SO-DIMM, up to 8GB
- 1x DVI-I, 1x HDMI, 1x GbE and 5.1 channel audio output
- SATA HDD or SSD, 1x eSATA & USB Combo Connector,
- 3-in-1 card reader and 5x USB
- Optional WIFI+Bluetooth Module or 3G Module



Product Overview

The KUBE-8060 is a surprisingly affordable, space-saving box player with powerful computing and graphic performance to turn your living room into home theater with ease.

Featuring the latest 32 nm Intel® Capella platform with intel® HM55 chipset, integrated the industrial X86 SBC and a rugged design make it quick to deploy and easy to manage your digital signage network.

Technical Information

Construction
Aluminum Housing
System Board
Proprietary motherboard, Intel® Calpella platform Support Arrandele rPGA socket type processor with HM55 express chipset
Memory
2x DDR3 800/1066 SO-DIMM up to 8GB
I/O Panel
Front I/O
3x 3.5mm Phone Jack, support 5.1 channel audio output
1x eSATA and USB 2.0 combo connector
3x USB 2.0
1x Power LED
1x Storage status LED (HDD/Card reader)
1x Wifi status LED
1x Reset Button
1x Power Button
1x 3 in 1 Card Reader (SD / MMC / MS)
Rear I/O
1x DC JACK
1x DVI-I for DVI-D or VGA output
1x HDMI (V1.3 compatible)
1x RJ-45 GbE port
2x USB 2.0
1x COM Port support RS-232/422/485 (Offer +5V/+12V selection)
2x Wifi external antenna
1x 3G external antenna
1x S/PDIF Output

Storage
1 x 2.5" SATA HDD or SSD
Power Adapter
Input: 100-240 VAC, 50-60 Hz Output: 12V/5.4A 65W
Expansion Slot
2 x half size mini PCIe slot (Optional for 3G/WiFi+Bluetooth module) 1x SIM card slot (for 3G appliance) support user accessible
Cooling
Fanless
Temperature / Humidity
Operating: 0°C to 40°C, 0%-90%, non-condensing Storage: -20°C to 80°C, 0%-90%, non-condensing
Dimensions
260 x 153.3 x 57.8 mm (WxDxH)
Weight
TBD
Mounting
Desktop, VESA-mount
Certifications
CE/FCC Class A

KUBE-8060 I/Os

